

产品规格书 製品規格書 Product Technical Data Sheet

产品名称: 铝箔胶带 製品名称: アルミホイルテープ Part name: Foil tape
 产品型号: KBL-A01 製品番号: KBL-A01 Part code: KBL-A01
 颜色: 银色 色: 银 Color: Silver
 材料: 铝箔(AL foil)+丙烯酸压敏胶 Materials: Aluminum foil + Acrylates copolymer
 产品特点: 耐高温和隔热性能。
 製品特性: 高温および断熱。
 Characteristics: High temperature and thermal insulation.

参数 パラメーター Parameter	测试标准 テスト基準 Testing standard	值 值 Data
标称宽度 幅 Width	-	19/25mm ±0.2
标称厚度 厚さ Thickness	-	0.10mm±0.02
180°剥离力 180°引きはがし粘着力 180°peel-off strength	ISO 29862	≥1.5N/cm
拉伸强度 引張強さ Tensile strength	ISO 29864	≥15N/cm
断裂伸长率 伸び Stretch performance	ISO 29864	≥5%
耐温等级 耐温等級 Temperature resistance	GMW 16740	-40°C (4h)~220°C (3000h) 245°C (240h)
阻燃性能 難燃性能 Flame retardation	ISO 3795	Class B 自熄 自然に消えること self-extinguishing

其它信息 Additional information:

标准长度: 25M±0.3/卷 Standard length: 25M±0.3/roll
 纸芯内直径: 38mm±1 Core diameter: 38mm±1
 长度、宽度可定制 Further dimensions are available upon request.

耐磨等级(刮磨) Abrasion class (Scrape)

Abrasion class	Requirement
A no abrasion protection	< 100 strokes
B little abrasion protection	100 - 499 strokes
C medium abrasion protection	500 - 999 strokes
D high abrasion protection	1 000 - 4 999 strokes
E very high abrasion protection	5 000 -14 999 strokes
F extremely high abrasion protection	15 000 - 29 999 strokes
G abrasion protection for special applications	≥ 30 000 strokes

阻燃等级 Flame class

Fire class	Requirement
A (not flammable)	The flame goes out as soon as the burner is removed.
B (self-extinguishing)	The flame goes out before the first reference mark is reached.
C	Burning rate ≤ 100 mm/min
D	Burning rate > 100 mm/min