

产品规格书 製品規格書 Product Technical Data Sheet

产品名称: PVC 胶带 製品名称: PVCテープ Part name: PVC tape
 产品型号: KBL-P06 製品番号: KBL- P06 Part code: KBL-P06
 颜色: 黑色 色: 黒 Color: Black

材料: PVC+丙烯酸压敏胶 Materials: PVC + Acrylates copolymer

产品特点: 极佳的柔韧性和阻燃性能, 万能型包裹用胶带。极易手撕。

Characteristics: Excellent flexibility and flame retardation performance, universal wrapping tape. Hand-tearable.

参数 パラメーター Parameter	测试标准 テスト基準 Testing standard	值 值 Data
标称宽度 幅 Width	-	9/19/25/32/38/50mm±0.2
标称厚度 厚さ Thickness	-	0.10mm±0.02
180°剥离力 180°引きはがし粘着力 180°peel-off strength	ISO 29862	≥3N/19mm
拉伸强度 引張強さ Tensile strength	ISO 29864	≥19.6N/19mm
断裂伸长率 伸び Stretch performance	ISO 29864	≥100%
耐温等级 耐温等級 Temperature range	GMW 16740	-40°C(4h)~105°C(3000h) 125°C(240h)
耐电压 耐電性 Withstand voltage	GMW 16740	AC 1000V,1min
阻燃性能 難燃性能 Flame retardation	GMW 16740	Class B 自熄 自然に消えること self-extinguishing

其它信息 Additional information:

标准长度: 25M/卷 Standard length: 25M/roll

纸芯内直径: 38mm±1 Core diameter: 38mm±1

长度、宽度可定制 Further dimensions are available upon request.

阻燃等级 Flame class

Fire class	Requirement
A (not flammable)	The flame goes out as soon as the burner is removed.
B (self-extinguishing)	The flame goes out before the first reference mark is reached.
C	Burning rate \leq 100 mm/min
D	Burning rate $>$ 100 mm/min