

产品规格书 Product Technical Data Sheet

名称: 布基胶带 製品名称: 繊維テープ Part name: Cloth tape

型号: KBL-T03 製品番号: KBL-T03 Part code: KBL-T03

颜色: 黑色 色: 黒 Color: Black

材料: 针织布(PET)+丙烯酸压敏胶 Material: Woven PET + Acrylates copolymer

特点: 耐温等级高, 适用于高耐温低耐磨要求的线束。包裹性好, 易手撕。

製品特性: 良い耐高熱性能と低耐磨性。手で引き裂くこと。

Characteristics: High temperature resistance. Universal wrapping tape, Hand-terable.

参数 パラメーター Parameter	测试标准 テスト基準 Testing standard	值 值 Data
标称宽度 幅 Width	-	9/19/25/32/38/50mm±0.2
标称厚度 厚さ Thickness	-	0.16mm±0.02
180°剥离力 180°引きはがし粘着力 180°peel-off strength	ISO 29862	≥1.5N/cm
拉伸强度 引張強さ Tensile strength	ISO 29864	≥20N/cm
断裂伸长率 伸び Stretch performance	ISO 29864	≥10%
耐温等级 耐温等級 Temperature resistance	GMW 16740	-40°C(4h)~125°C(3000h) 150°C(240h)
耐磨性能(刮磨) 耐磨性能(針磨) Abrasion resistance (Scrape)	ISO 6722	Class B 100~499
阻燃性能 難燃性能 Flame retardation	GMW 16740	Class B 自熄 自然に消えること self-extinguishing

其它信息 Additional information:

标准长度: 20M±0.3/卷 Standard length: 20M±0.3/roll

纸芯内直径: 38mm Core diameter: 38mm

长度、宽度可定制 Further dimensions are available upon request.

耐磨等级(刮磨) Abrasion class (Scrape)

Abrasion class	Requirement
A no abrasion protection	< 100 strokes
B little abrasion protection	100 - 499 strokes
C medium abrasion protection	500 - 999 strokes
D high abrasion protection	1 000 - 4 999 strokes
E very high abrasion protection	5 000 -14 999 strokes
F extremely high abrasion protection	15 000 - 29 999 strokes
G abrasion protection for special applications	≥ 30 000 strokes

阻燃等级 Flame class

Fire class	Requirement
A (not flammable)	The flame goes out as soon as the burner is removed.
B (self-extinguishing)	The flame goes out before the first reference mark is reached.
C	Burning rate ≤ 100 mm/min
D	Burning rate > 100 mm/min