

## 产品规格书 製品規格書 Product Technical Data Sheet

产品名称：布基胶带 製品名称：纖維テープ Part name: Cloth tape

产品型号：KBL-T04(O) 製品番号：KBL-T04(O) Part code: KBL-T04(O)

颜色：橙色 色：オレンジ Color: Orange

材料：PET+丙烯酸压敏胶 Material: PET + Acrylates copolymer

特点：超强的耐磨性能和耐高低温性能，全车线束适用，特别适用于耐磨和耐高温要求高的发动机线束。不可手撕。

製品特性：良い耐磨性と耐高低温性能、全車 Harnessに適用すること、特に高耐磨と高耐温のENGROOM HarnessとENGINE Harnessに適用すること。手で引き裂かないこと。

Characteristic: Super abrasion resistance and high temperature resistance, can be used for anywhere especially for engine harness. Not hand-tearable

参数 パラメーター Parameter	测试标准 テスト基準 Testing standard	值 值 Data
标称宽度 幅 Width	-	9/19/25/32/38/50mm±0.2
标称厚度 厚さ Thickness	-	0.25mm±0.02
180°剥离力 180°引きはがし粘着力 180°peel-off strength	ISO 29862	≥1.5N/cm
拉伸强度 引張強さ Tensile strength	ISO 29864	≥40N/cm
断裂伸长率 伸び Stretch performance	ISO 29864	≥10%
耐温等级 耐温等級 Temperature resistance	GMW 16740	-40°C(4h)~150°C(3000h) 175°C(240h)
耐磨性能(砂磨) 耐磨性能(砂磨) Abrasion resistance (Sand paper)	ISO 6722	>1200mm
耐磨性能(刮磨) 耐磨性能(針磨) Abrasion resistance (Scrape)	ISO 6722	Class D 1000~4999
阻燃性能 難燃性能 Flame retardation	GMW 16740	Class B 自熄 自然に消えること self-extinguishing

其它信息 Additional information:

标准长度: 25M±0.3/卷 Standard length: 25M±0.3/roll

纸芯内直径: 38mm±1 Core diameter: 38mm±1

长度、宽度可定制 Further dimensions are available upon request.

耐磨等级(刮磨) Abrasion class (Scrape)

Abrasion class	Requirement
A no abrasion protection	< 100 strokes
B little abrasion protection	100 - 499 strokes
C medium abrasion protection	500 - 999 strokes
D high abrasion protection	1 000 - 4 999 strokes
E very high abrasion protection	5 000 -14 999 strokes
F extremely high abrasion protection	15 000 - 29 999 strokes
G abrasion protection for special applications	≥ 30 000 strokes

阻燃等级 Flame class

Fire class	Requirement
A (not flammable)	The flame goes out as soon as the burner is removed.
B (self-extinguishing)	The flame goes out before the first reference mark is reached.
C	Burning rate ≤ 100 mm/min
D	Burning rate > 100 mm/min